


Maintenance-Free Bearing With Integrated Flange For Harsh Tillage

IL60-150/6T-M30x2

Maintenance-Free Bearing With Integrated Flange For Harsh Tillage
Disc Harrow



Technical Specification

J	Pitch circle diameter	150 mm
D	Outside diameter	178 mm
H/T	Hole/Thread	6xM12x1.25 mm
d	Bore diameter	35 mm
C	D-shape hole cut out dimension	32.5 mm
M	Outer Thread	M30x2 mm
L	Total length	126.5 mm
L1	Total flange length	63 mm
E	Length of D shape	23.5 mm
F	Length of threaded part	40 mm
kg	Mass	4.573 kg
C _{dyn}	Dynamic load rating	75.86 kN
C _o	Static load rating	66.2 kN
P _u	Fatigue load limit	2.78 kN

Sealing

O-RING+ SHEET METAL SHIELD+S SEAL / S SEAL+DIRTBLOCK SEAL+FORGED COVER PLATE

O-ring, Sheet metal shield and S seal on the base side and S seal, Dirtblock seal with Forged cover plate on the front side which is exposed to contaminants.

O-ring, Sheet metal shield and S seal together with attached disc eliminates the possibility of contamination from the base side.

Dirtblock seal is designed for hard working condition at unfriendly environment. Half metal - half rubber outside diameter provides reliable seal retention in the bore and improves sealing performance. Inside diameter is covered by rubber and improves sealing performance and easy installation. Forged cover plate is additional, strong protection of the Dirtblock seal against mechanical damage.

This sealing provides maximum protection against liquid or solid contaminants, which significantly extends bearing service life.

